

ESCORTS Forklift

... Economical, Efficient & EuroII Compliant



A wide national network of Business Centres and Dealers

- **Ahmedabad** : (079) 40063445, 9879006280 • **Bangalore** : (080) 23398809, 9980945232 • **Bhopal** : (0755) 2551955, 9826824111
- **Bhubaneswar** : (0674) 2588775, 9937028870 • **Chandigarh** : (0172) 5017995, 9779159900 • **Chennai** : (044) 42153707,9840852996
- **Dehradun** : (0135) 2672647, 9837755999 • **Guwahati** : (0361) 2733246, 9821458206 • **Hyderabad** : (040) 27842451, 9849992003
- **Jaipur** : (0141) 2760904, 9799495223 • **Kanpur** : 9839211591 • **Kolkata** : (033) 24862028,9830108037 • **Lucknow** : (0522) 4003683, 2371901, 9919621222
- **Mumbai** : (022) 24218150, 9821458206 • **Nagpur** : (0712) 6450713, 9822224489 • **New Delhi** : (011) 26444821, 9871598288
- **Pune** : (020) 40089771, 9764007100 • **Ranchi** : (0651) 27842451, 9771906141 • **Visakhapatnam** : (0891) 2563235, 9866637270

ESCORTS CONSTRUCTION EQUIPMENT LIMITED

Plot No: 219, Sector-58, Faridabad-121 004, Haryana, India
Tel.: (0129) 2306568, 2306578 Fax: 2306566 Mobile: 9810299587, 9873543535
E-mail: marketing@escorts-ecel.com, Website: www.ecel.com

• The information contained in this leaflet is intended to be of a general nature only. • We reserve the right to change specification without notice. • All dimensions and Weight are variable within +/-5%.

2.0 - 3.5 T Engine Powered



World's top 10

Product:

- Best Indian manufactured Forklift: Technology & Specifications
- Multiple offerings in 2.0-3.5 T range
- Application/duty specific model
- ECEL after sales support - 88 locations
- More than 13 years presence in the forklift industry

Performance:

- Best Indian Manufactured Forklift - Performance
 - Productivity
 - Lowest Cost per unit Material handled
 - Reliability
- Customized for Indian conditions

Specifications

Model		Units	CPCD20 - HJ	CPCD25 - HJ	CPCD30 - HJ	CPCD35 - HJ
Load Capacity		Kg	2000	2500	3000	3500
Rated Load Centre		mm	500			
Power Type			Diesel			
Tyre Type			Pneumatic (Optional: Solid)			
Tyre Size (F/R)			7.00-12-12PR/6.00-9-10PR		28x9-15-12PR/6.50-10-10PR	
Maximum Fork Height	B	mm	3700			
Free Lift	E	mm	155		160	
Fork Size (TxLxW)	F	mm	40/1070/122		45/1070/125	50/1070/125
Tilt Angle (F/B)	Y	Deg	6° - 12°			
Overall Length (With Fork)	H	mm	3550	3620	3745	3765
Overall Length (Without Fork)	I	mm	2480	2550	2675	2695
Overall Width	Q	mm	1150		1225	
Overhead Guard Height	P	mm	2070		2090	
Overall Height of Mast	C	mm	2355		2415	2530
Min. Turning Radius	W	mm	2170	2240	2400	2420
Min. Intersecting Aisle	X		1920	2010	2110	
Maximum Travel Speed		Km/h	19			
Lifting Speed (With Load/Without Load)		mm/sec	550/600		450/470	330/370
Maximum Gradeability		%	20	19		16
Total Weight		kg	3410	3770	4370	4900
Wheel Base	L	mm	1600		1700	
Min. Underclearance	G	mm	110		140	135
Lateral Fork Adjustment	R	mm	245-1020		250-1060	
Engine Model			HJ493			
Battery Voltage/Capacity		V/Ah	12/105			



